



LBR iisy 15 R930



Basic data

Kinematic type	Articulated robot
Cobot	Yes

Safety requirements	Category 3 and Performance Level of
	in accordance with EN ISO 13849-1

Technical data

Maximum reach	930 mm
Rated payload	15 kg
Maximum payload	16.41 kg
Pose repeatability (ISO 9283)	± 0.05 mm
Number of axes	6
Mounting position	Floor;
	Ceiling;
	Wall;
	Desired angle
Footprint	275 mm x 275 mm
Weight	approx. 43.2 kg

Axis data

Motion range	
A1	±185 °
A2	-230 ° / 50 °
A3	±150 °
A4	±180 °
A5	±110 °
A6	±220 °
Speed with rated payload	
A1	200 °/s
A2	200 °/s
A3	200 °/s
A4	230 °/s
A5	260 °/s
A6	380 °/s

Operating conditions

Ambient temperature during operation	0 °C to 45 °C (273 K to 318 K)
--------------------------------------	--------------------------------

Protection rating


Protection rating	(IEC 60529)	IP54

Controller


Controller	KR C5 micro
Controller	KK C5 IIICIO

Certificates

Workspace graphic




Payload diagram



The LBR iisy 15 R930 is designed for a rated payload of 15 kg in order to optimize the dynamic performance of the robot. The maximum payload of 16.41 kg only applies if the position of the center of mass is 0 mm. The specific load case must be verified using KUKA.Load or KUKA Compose. For further consultation, please contact KUKA Support.

Mounting flange



The robot has an internal energy supply system from axis 1 to axis 6 for use by the customer with 8 control cables and a 1 Gbit Ethernet cable.

Details provided about the properties and usability of the products are purely for information purposes and do not constitute a guarantee of these characteristics. The extent of goods delivered and services performed is determined by the subject matter of the specific contract. No liability accepted for errors or omissions.

0000-366-983 / V1.1 / 22.02.2023 / en